
TREMBOVEL'SKIY, Dmitriy Evanovich; ZANEVSKIY, H.S., redaktor; SOKOL'SKIY, I.F., redaktor; KONYASHINA, A., tekhnicheskiy redaktor.

[Hydraulic rams for simple water supply lines] Gidravlicheskie tarany dlia prostykh vodoprovodov. Moskva, Izd-vo Ministerstva kommubal'nogo khoziaistva RSFSR, 1956. 96 p. (MIRA 9:6)

(Hydraulic rams) (Water supply, Rural)

	12_32_31_65 EAT(d)/EAT(1)/EXD-2/12(h) Pab	
	ACCESSION NR: AP5007031 S/0120/65/000/001/0086/008)	
	AUTHOR: Golutvin, I. A.; Zenevskiy, Yu. V.	830
	TITLE: Nanosecond coincidence circuit using transistors and tunnel diodes 2	
	SOURCE: Pribory i tekhnika eksperimenta, no. 1, 1965, 86-89	
	TOPIC TAKE: cordel cable transmission, pulse shaper, coincidence circuit, phyto-	
	muctiplier tunel diode discriminator	
	ABSTRACT: A sensitive two-channel coincidence circuit for scintillation count is proposed with a view toward reducing pulse distortion in signal transmission U.	
	over coaxial cables. Essentially, the circuit consists of two pulse shapers and a discriminator and operates on the orinciple of summation of signals which ar	1 2
	tunne. diode. The resolving time of the circuit, measured with Co ⁵⁰ and Ne ²²	5
	sources, was approx 1.5 namesec. The dead time of a channel on the basis of dial	
	pulses was approx 10 rancsec. The secsitivity of the circuit can be as high cut 50-100 mv. Orig. art. has: 11 figures. [JR	
	ASSOCIATION: Ob"yedinennyy institut yadernykh issledovaniy (Joint Muclear Resuarce Institute)	h o
and the sales bear and	ard 1/2	

"APPROVED FOR RELEASE: 09/19/2001 CIA-RDP86-00513R001963810003-0



properties to the control of the con ACCESSION UR: AP4047469 23060)/201/420/ 5/0120/64/000/005/0114/0119 AUTHOR: Galutyin, I. A.; Zanevskiy, Yu. V. CITLE: A system of universal modules for scintillation counters SOURCE: Pribory* i tekhnika eksperimenta, no. 5, 1964, 114-119 TOPIC TACS: universal module, scintillation counter, pulse chapter, tunnol midde, coincidence dircuit, unticoincidence dircuit. CaAs tuonel winde, wide bund amplifier, common emitter circuit AUSTRACT: The following four universal circuits to be used with seine liation counters have been developed; 1) The first shaping circult whose basic function is the standardization of phisas at the scintillation counter dutput. It utilizes three transistors, one of thich is biased with a current of ~5 mamp and protects against over-loads, while the other two insure the power amplification of the limited signal. The output signal of the first shaping circuit in either a positive or a tegative pulse of ~ 10 nsec in duration and ~ 0.4 v in height. The dead time is ~ 30 nsec. 2) Next is a four Card 1/2

L 14574-65 ACCESSION MR: AP4047469

channel coincidence or anticoincidence sircuit which utilizes four diodes. The application of negative pulses produces coincident mode of operation while the utilization of positive pulses results in the anticoincident mode of operation. 3) A second shaping circuit is connected after the coincidence circuit and functions as a discriminative utilizes a monostable multivibrator based on a GaAs tunnel diode. The output light of the circuit is a negative pulse of to near durition and 0.7 a height. The output impedance is 50 ohms, 4) The vice-band amplifier consists of three common emitter transistors. The first two transfators are dre coupled while the third uses an emicter-follower circuit. The amplifier gain is 8, the pulse rise time is several needs. The output impedance is 50 ohms. Torig, art, has: 14 figures.

ASSOCIATION: Ob'yedinennyy institut yadernykh iasladovaniy (joint Institute of Nuclear Research).

SUBMITTED: 050cc63

ENGL: 00

SUB CODE: EC

NO REF SOV. 1000

OTHER: 002

Line 2/2

GOLUTVIN, I.A.; ZANEVSKIY, Yu.V.

System of universal moduli for scintillation counters. Prib.
1 tekh. eksp. 9 nc.5:114-119 S-0 '64. (MIRA 17:12)
1. Ob"yedinennyy institut yadernykh issledovaniy.

HUNGARY

ZANCEL, Vera, Dr, MASSZI, Jozsef, Dr; Medical University of Budapest, Dermatological and Venereclogical Clinic (director: FOLDVARI, Ferenc, Dr) (Budapesti Orvostudomanyi Egyetem, Bor-Nemikortani Klinika).

"Three Cases of Steroid Diabetes Leading to Ketosis."


Budapest, Orvosi Hetilap, Vol 108, No 9, 26 Feb 67, pages 395-396.

Abstract: [Authors' Hungarian summary] Three cases of steroid diabetes involving transient ketosis, an occurrence not previously reported in the literature, are described. On the basis of the clinical symptoms and laboratory findings, the ketosis can be accepted as documented. In addition to the exhaustion of insulin reserves, other metabolic disturbances may also contribute to its development. Attention is called to the importance of an adequate evaluation of the early precomatous symptoms and of a routine testing for acetone in the urine. All 5 references are Hungarian.

FEHER, L., dr.; ZANGEL, V., dr.

Treatment of steroid diabetes with oradian. Ther. Hung. 13 no.1:
17-20 '65


1. 2nd Department of Medicine (Director: Prof. P. Gomori), and
Department of Dermatology (Director: Prof. F. Foldwari),
University Medical School, Budapest.





 Dokl.All A2	erb. Sin to no	rrence of cert .4:377-379 160	•		
1. Institu G.A. Aliye	it botaniki Al	AzerSSR. Predical jan-Botany	stavleno akad	l. AN AzerSSR	
00 0 					
	. V				
					. 0

ZANGIYEV, M. G., CAND BIO SCI, "SEASONAL DYNAMICS OF LITTER RESERVES OF THE MOST PREDOUTHANT TYPES OF BEECH POST REGENERATION PROCESSES." FOREST AND ITS IN BAKU, 1961. (COMPOR HIGHER AND SEC SPEC ED OF THE COUNCIL OF MINISTERS AZSSR. AZERBAYDZHAN STATE UNIV IMENI S. M. KIROV. ACAD SCI AZSSR. INST OF BOTANY IMENI V. L. KOMAROV). (KL-DV, 11-61, 214).

-82-







5/094/61/000/007/001/005 E073/E335 Zangurin, Sh.M., Gordeyev, N.V. and Flaskless Casting of Precision Cast Blocks Promyshlennaya energetika, 1961, No. 7, Tsyngalov, V.D. AUNHORS: In one of the undertakings precision casting by the TEXT: In one of the undertakings precision casting by prior float wax method was carried out by placing the moulds, prior float wax method was carried out by placing the moulds, prior float wax method was carried out by placing the moulds, prior float wax method was carried out by placing the moulds, prior float wax method was carried out by placing the moulds, prior float wax method was carried out by placing the moulds, prior float wax method was carried out by placing the moulds, prior float wax method was carried out by placing the moulds, prior float wax method was carried out by placing the moulds. to teeming of the metal, into flasks which were then filled to teeming of the metal, essential since the moulds were with dry sand. TITLE: to teeming of the metal, into flasks which were then fill with dry sand. This was exhaust since the moulds were produced from hydrolized exhaust state and in soit of PERIODICAL: with dry sand. This was essential since the moulds were produced from hydrolized ethyl silicate and in spite of produced from hydrolized ethyl silicate and in spite of enough.

applying four refractory coatings they were not strong furnace heated in an electric furnace. applying four refractory coatings they were not strong enough the flasks were heated in an electric furnace Before teeming, the flasks were heated in an electric furnace to 900-950 C. The authors proposed a new technology to 900-950 C. The authors proposed the necessity of use the proposed authors and obvious the necessity of use the proposed authors are constituted to the necessity of use the necessity of the proposed authors are constituted to the necessity of use the necessity of the necessi to 900-950 °C. The authors proposed a new technology which consured sufficient strength and obviated the necessity of with flasks. In the same way as before, the moulds were coated with ensured sufficient strength and obviated the necessity of using with the same way as before, the moulds were coated with flasks. In the same way as two of which contained liquid glass. four layers of refractory. flasks. In the same way as before, the moulds were coated with four layers of refractory, two of which contained liquid glass. The layers with liquid glass were deposited on the ethylfour layers of refractory, two of which contained liquid glass were deposited on the ethylThe layers with liquid glass were deposited on These layers
silicate films and acted as reinforcing layers. ing layers with liquid glass were deposited on the silicate films and acted as reinforcing layers. Cará 1/4

APPROVED FOR RELEASE: 09/19/2001

CIA-RDP86-00513R00196381

S/094/61/000/007/001/005 E073/E335

Flaskless Casting

contained: liquid glass; quartz powder (artificial marshallite); refractory clay; hydrochloric acid. Before preparing the rendering the modulus of the liquid glass had preparing the rendering the modulus of the liquid glass had to be increased to 3 to 3.5 by adding hydrochloric acid to it. The quantity of hydrochloric acid per 1 litre of liquid glass should be as follows:

Modulus of the liquid glass 2.6 2.7 2.8 2.9 3.0 100% hydrochloric acid, 25 20 17 12.8

The acid has to be diluted with water before adding it to liquid glass. The specific weight of the liquid glass, which is diluted with hydrochloric acid, should be 1.2 - 1.25. On the refractory clay was roasted in the furnace at 500-600 °C. The refractory clay was roasted in the furnace at 500-600 °C. The for 2-5 hours and passed through a sieve No. 40. The marshallite was passed through a sieve No. 40 without processing. The rendering was prepared by simple mixing of the liquid. The rendering was prepared by simple mixing of the liquid.

Card 2/4


S/094/61/000/007/001/005 E073/E335

Flaskless Casting

Before use, the rendering should be passed through a 12-20 sieve to remove lumps. Sequence of the operations:

- 1) dipping of the mould block into the tank containing the rendering;
- 2) producing a uniform layer of rendering throughout the entire surface;
- 3) spraying of the block with dry quartz sand;
- 4) cleaning of the edges of the boat mould from the rendering;
- 5) drying of the block for four hours at 25 50 °C. As a result of using this method, ceramic moulds with a satisfactory strength were obtained which were able to withstand firing in the furnace at temperatures up to 800-900 °C. Mould blocks produced by this method do not require the use of flasks and, as a result, it is possible to increase considerably the number of moulds charged into the firing furnace and to reduce the firing time, since the thin ceramic blocks are heated much more quickly than moulds placed into heavy sand-filled from mould boxes. To maintain a stable position during teeming the mould is placed into a dry-sand bed, as shown in

Card 5/4



The roads of technical progress in the Soviet textile industry in the period (FRZEMYSL WLOKIENWICZY. Vol. 10, no. 9, Sept. 1956, Lodz, Poland) of the sixth Five-Year Plan. p. 120.

SO: Monthly List of East European Accessions (EEAL) LC. Vol. 6, No. 12, Dec. 1957. Uncl.

POLUID / Chemical Technology. Chemical Products and Their Applica-

APPROVED FOR RELEASE: 09/19/2001 CIA-RI This Jour : Ref Zh Khiza., No 12, 1959, No 44342


Author : Zeniemojski, J. Inst : Not given

: The Future of Synthetic Fibers Title


Orig Pub : Techn. wlokienn., 1958, No 9, 273-274

Abstract : None given

Card 1/1



ZANTEWSKI, E. Changes in the turnover of grain, with regard to the new General Conditions of Delivery. p. 4 (Rolink Spoldzielca. Vol. 9 (i.c. 10) no. 13, Mar. 1957. Warszaw, Poland) Menthly Index of East European Accessions (EEAI) LC. Vol. 7, no. 2, February 1958





ZANIEWSKI, H.


For the correct procedure of purchasing grain of the 1957 crop.


p. 7 (Rolnik Rolnictwo) Vol. 9, No. 13, Oct. 1957, Warszawa, Poland


SO: MONTELY INDEX OF EAST EUROPEAN ACCESSIONS (EEAI) LC, VOL. 7, NO. 1. JAN. 1958











ZANGER, A. Shall we drive more safely in our country at night, also? p. 376

Vol. 10, no. 12, 1956, June
SVET MOTORU
TECHNOLOGY
Praha, Czschoslovakia

So: East European Accession Vol. 6, no. 2, 1957

"APPROVED FOR RELEASE: 09/19/2001

CIA-RDP86-00513R001963810003-0

USSR/Medicine - Prophylaxis Jun 1947
Medicine - Bacteriology

"Some Prophylactic Measures in Anaerobic Infection,"
T. Kh. Zengiyev, 5 pp

"Voyenno Med Zhur" No 6

Discussion, with statistical table, to the effect that general sanitary measures are very important in enserobic prophylaxis, that a wound should be treated immediately, with injection of 5 doses of anti-gangrene serum, etc.


14788


ZANGIEV, T. KH.


Professor N. A. Bogoraz. Fel'dsher & akush. No. 11, Nov. 50.
p. 36-41

1. Candidate Hedical Sciences.

CIMI 20, 3, March 1951








"APPROVED FOR RELEASE: 09/19/2001

CIA-RDP86-00513R001963810003-0



ZANIEMOJSKI, J.

ZANIEMOJSKI, J. Problems of scientific-technical documentation in the textile industry. p. 101

Vol. 10, no. 2, 1956 PRZEMYSL WLOHIENNICZY TECHNOLOGY Lods, Poland

So: East European Accession Vol. 6, no. 2, Feb. 1957

ZANJKO, A. M.
"Essai d'utilisation de solutions non aqueuses dans la polarographie".,
Zanjko, A. M. et Manusova, F. A., (p. 1171)

SO: Journal of General Chemistry (Zhurnal Obshchei Khimii) 1940, Volume 10, no. 13.

ACCESSION NR: AP4041639

\$/0114/64/000/006/0039/0040

AUTHOR: Troyanovskiy, B. M. (Candidate of technical sciences, Docent); Zanin, A. I.; Kazintsev, F. V. (Engineer)

TITLE: Higher economy of a stage in which stamped blades were replaced with milled blades

SOURCE: Energomashinostroyeniye, no. 6, 1964, 39-40

TOPIC TAGS: steam turbine, steam turbine blade, stamped turbine blade, milled turbine blade, steam turbine economy

ABSTRACT: The last stage of a VPT-25-4 (Ural Turbomotor Plant) steam furbine was tested under various conditions with (a) stamped nozzle blades and (b) MEI-designed milled varying-thickness blades having the same effective $\sin \alpha_1 = 0.266$. The stage efficiency was 80-81% and 86% for the first and second diaphragms, respectively. The tests were staged with pressure ratios

Card | 1/2

ACCESSION NR: AP4041639

corresponding to subsonic speeds in the diaphragms, and with natural Reynolds numbers [Re = b, c, $/\sqrt{}$, = $(1.3-2.0)\times10^5$]. Orig. art. has: 2 figures.

ASSOCIATION: Moskovskiy energeticheskiy institut (Moscow Power-Engineering

SUBMITTED: 00

ENCL: 00

SUB CODE: PR

NO REF SOV: 002

OTHER: 000

Card 2/2

GOLOVIN, V.A., inzh., dissertant; ZANIN, A.I., inzh.; KAZINTSEV, F.V., inzh., dissertant

Methods for studying models of the terminal stages of steam turbines operating on wet steam. Teploenergetika 12 no.3:71-75 Mr 165. (MIRA 18:6)

1. Moskovskiy energeticheskiy institut.

KAZINTSEV, F.V., inzh.; TROYANOVSKIY, B.M., kand.tekhn.nauk; ZANIN, A.I., inzh.


Study of a stemm turbine stage with d/l=2,75. Teploenergetika
12 no.1:35-39 Ja '65.

1. Moskovskiy emergeticheskiy institut.

TROYANOVSKIY, B.M., kand. tekhn. nauk, dotsent; KAZINTSEV, F.V., inzh.;

ZANIN, A.I., inch.


Increase of stage efficiency resulting from the replacement of stumped nozzle blades with milled ones. Energomashinostroenie
10 no.6:39-40 Je '64. (MIRA 17:9)



VOLKOV, Yu.I., inzh.; GAFANOVICH, A.A., kand.tekhn.nauk; GLADKOV, N.G., kand.sel akokhoz.nauk; GORKUSHA, A.Ye., agr.; ZHITNEY, N.F., inzh.; ZANIN, A.V., kend.tekhn.nauk; ZAUSHITSYN, V.Ye., kand.tekhn.nauk; ZVOLINSKIY, H.F.; ZEL'TSERMAN, I.M., kand.tekhn.nauk; KAIPOV, A.N., kend.tekhn.nauk; KASPAROVA, S.A., kend.sel'skokhoz.nauk; KOLOTUSHKINA, A.P., kend.ekon, nauk; KRUGLYAKOV, A.M., inzh.; KURNIKOV, I.I., inzh.; LAVRENT'YEV, L.N., inzh.; LEBEDEV, B.M., kand.tekhn.nouk; LEVITIN, Yu.I., inzh.; MAKHLIN, Ye.A., inzh.; NIKOLAYEV, G.S., inzh.; POLESHCHENKO, P.V., kand. tekhn. nauk; POLUNOCHEV, I.M., agr.; P'YANKOV, I.P., kand.sel'skokhoz.nauk; RABINOVICH, I.P., kand.tekhn.nauk; SOKOLOV, A.F., kend.sel'skokhoz.nauk; STISHKOVSKIY, A.A., inzh.; TURBIN, B.G., kand. tekhn. neuk; CHARAN, I.V., inzh.; CHAPKEVICH, A.A., kand. tekhn. nauk; CHERNOY, G.G., kand. tekhn. nauk; SHMELRY, B.M., kand. tekhn.nauk; KRASNICHENKO, A.V., inzh., red., KLETSKIN, M.I., inzh., red.; MOLYUKOV, G.A., inzh., red.; HLAGOSKLONOVA, N.Yu., inzh., red.; UVAROVA, A.F., tekhn.red.


[Reference book for the derigner of agricultural machinery in two volumes] Spravochnik konstruktora seliskokhoziaistvennykh mashin v dvukh tomakh. Moskva. Gos.nauchno-tekhn.izd-vo mashinostroit. lit-ry. Vol.1. 1960. 655 p. (MIRA 13:11) (Agricultural machinery-Design and construction)

22519	Zanin, A. V. Uluchsheniye Konstruktsii Samokhodnogo Kombaina S-4. Sel'Khozmashina, 1949, No. 7, S 4-4
so:	Letopis' No. 30, 1949



ACC NR. A	AVSO26550	
	Gafanovich, A. A.; Zanin, A. V.; Vidishev, B. G.; Filimon	/019/0114/0114
ORG: none	v.; vloishev, B. G.; Filimon	ov, V. N.
TITLE: Car	rdan shaft with protective housing. Class 47, No. 175358	7
TOPIC TAGS:	Cardan shaft, universal joint	
a protective and joints whousing's re	in Author Certificate has been issued for a Cardan shaft of housing in the form of a telescoping tube with hemisphere with grooved yokes. To better protect the Cardan shaft and tation, the housing is equipped with outer hemispheres compleres by rings located in the universal joint's plane of we and mounted on smalled ball bearings installed on the hubs	a shaft,
	11,44	or the grooved

	UDG: 621-76-233.1.825.6	
		0/ 1209



EMP(K)/EMA(c)/EMI(d)/EMI(m)/EMP(h)/EMP(h)/EMP(l)/EMP(v)/EMP(t)L.**6**928-66 ACCESSION TRE AT5016185 JD/HW UR/3104/65/000/006/0042/0055 Zanin, A. Ya. (Engineer); Soloveychik, P. M. (Engineer) TITLE: Wheel rolling machine with horizontal positioning of the formed part SOURCE: Ural'skiy machinostròitel'nyy zavod, Sverdlovek. Nauchno-issledovatel'skiy institut tyazhelogo zashinostroyeniya. Proizvodstvo krupnykh zashin, no. 6, 1965. Prokatnoye obor idovaniye; konstruirovaniye, raschet i issledovaniye (Relling equipment; omstruction, design and investigation); sbornik statey, 42-55 TOPIC TIGS: matal forming, rolling mill, wheel forming, wheel rolling mill ABSTRACT: A wheel rolling machine with horizontal wheel positioning, which eliminates many of the dissidvantages of existing horizontal wheel rolling machines, is: described. In all, 13 disadvantages ranging from cycle speed to rolling accuracy are mentioned. Details of the design are shown in 5 detailed figures. The rolling station consists of a main roll and two inclined rolls with the former driven by a do notor and the latter driven through a common drive. The machine is equipped with an automatic loading, centering, and unloading table which displaces vertically and horizontally to clear all forming rolls. The machine has the following specifications: capacity - up to 150 railroad wheels/hour; 500-2500-m diameter parts; roll Card 1/2

	rpa - 130 1	for incli	ned rolls,	100 for	rain rol	ll; hydrau	ilic pres	sure 60-16	60 kg/ca²;	
	. 500 mm	a. inclin	ed:rolls.6	30 km 5	00 rpz: a	lecuracy -	- 0.2 # 2 :	per fead 1	min roll 250 revalution.	,
	Some of the	e advanta	gos of thi	e plibe o	f constru	ection are	discuss	ed. Orig.	. art. hası	
				<u>.</u>					4	455
	ASSOCIATIO	N: Ural	skiy mashi	ndatroit	al'nyy za	ivod, Svei mashinosi	rdlovsk (troveniva	(Scienti	ine works;; fic Research	1
	Institute	ot Heral	Machine Op	eration)	44.35	- HOGGILLIAG (ar o's arrain			
					ENCL	•			ib coder li	2
*,	SUBLUTIED:	00			- 54061	. 00				
	no ref sov	004	1.1	1	OTHER	000				
1		47 - 1				1.	17			
1						á	100	•		
. 1		**	*					•		
			,	. 1	, ,			à	•	
**								٠.	•	
		1	1			, ·				
	Card 1/2	nas			a Tayata iyo					
			14,535		وأصف سيدك أهوال	ورم مهجود ما الجانب المادية والماد المادية المادية المادية		16 33 33	The second secon	
				.1						
				15				- 1/		

"APPROVED FOR RELEASE: 09/19/2001 CIA-RDF

CIA-RDP86-00513R001963810003-0

ENT(d)/ENT(m)/ENP(v)/T/ENP(k)/ENP(h)/ENP(1) PJ UR/3104/65/000/006/0042/0055 ACCESSION NR: AT5018185 AUTHORS: Zanin, A. Ya. (Engineer); Soloveychik, P. M. (Engineer) TITLE: Wheel rolling machine with horizontal positioning of the formed part SOURCE: Ural'skiy mashinostroitel'nyy zavod, Sverdlovsk. Nauchno-issledovatel'skiy institut tyazhelogo mashinostroyeniya. Proizvodstvo krupnykh mashin, no. 6, 1965. Prokatnove oborudovaniye; konstruirovaniye, raschet i issledovaniye (Rolling equipment; construction, design and investigation); abornik statey, 42-55 TOPIC TAGS: metal forming, rolling mill, wheel forming, wheel rolling mill ABSTRACT: A wheel-rolling machine with horizontal wheel positioning, which eliminates many of the disadvantages of existing horizontal wheel rolling machines, is described. In all, 13 disadvantages ranging from cycle speed to rolling accuracy are mentioned. Details of the design are shown in 3 detailed figures. The rolling station consists of a main roll and two inclined rolls with the former driven by a do motor and the latter driven through a common drive. The machine is equipped with an automatic loading, centering, and unloading table which displaces vertically and horizontally to clear all forming rolls. The machine has the following specifications: capacity - up to 150 railroad wheels/hour: 500-2500-mm diameter parts; roll

	1			1							
<u>Y</u>	2011. Cession		r5018185	5				·• . · · · · ·			1
	· i.				00 6		untmant f	n meascul	n 60-11	60 <i>1ca/</i> er	2.
	ī	_ 1	10 m	mido T	K A m hi	main roll; h lgh; weight	→ 250 to	ono: no c	ns – m	am roi.	レムプリ
1	EDO -	um Ino	or back!	117a 1530) kw. 500) rom: accur	racy - 0	"S mm ber	read:	revolut.	1011*
Sc	oma of t	pe agan	ntagon c	of this	type of	construction	on are d	iscuspod	Orig	art.	nası ;
	figures			i							
		,		1							
	CONCTIMI	Otte IIv	al'skiy	mashin	stroitel	l'nyy zavod,	Sverdl	ovsk (Ur	al Mach	ine Wor	ks);
A.	SSOCIATI auchno-i	ON: Ur acledov	atel'ek:	ly insti	itut tya:	l'nyy zavod zhelogo masi	, Sverdl	ovsk (Ura yeniya (al Mach Scienti	ine Worl	ks); earch
A.	CONCTIMI	ON: Ur acledov	atel'ek:	ly insti	itut tya:	l'nyy zavod; zhelogo masi	, Sverdl	ovsk (Ura yeniya (al Mach Scienti	ine Worl	ks); earch
A: No	SSOCIATI auchno-i	ON: Ur scledov of Hea	atel'ek:	ly insti	itut tya:	l'nyy zavod, zhelogo masi ENCL: 00	ninostro	ovsk (Ura yeniya (3019HPT	ine Worl	Bad Oil
A. Ne In	SSOCIATI auchno-i netitute UBMITPEI	ON: Ur scledov of Hea : 00	atel. ek: vy liach:	ly insti	itut tya:	sperogo maar	ninostro	ovsk (Ura yeniya (3019HPT		Bad Oil
A. Ne In	SSOCIATI auchno-i netitute	ON: Ur scledov of Hea : 00	atel. ek: vy liach:	ly insti	itut tya:	ENCT: 00	ninostro	ovsk (Ura yeniya (3019HPT		Bad Oil
A. Ne In	SSOCIATI auchno-i netitute UBMITPEI	ON: Ur scledov of Hea : 00	atel. ek: vy liach:	ly insti	itut tya:	ENCT: 00	ninostro	ovsk (Ura yeniya (3019HPT		Bad Oil
A. Ne In	SSOCIATI auchno-i netitute UBMITPEI	ON: Ur scledov of Hea : 00	atel. ek: vy liach:	ly insti	itut tya:	ENCT: 00	ninostro	ovsk (Ura yeniya (3019HPT		Bad Oil
A. Ne In	SSOCIATI auchno-i netitute UBMITPEI	ON: Ur scledov of Hea : 00	atel. ek: vy liach:	ly insti	itut tya:	ENCT: 00	ninostro	ovsk (Ura yeniya (3019HPT		Bad Oil

"APPROVED FOR RELEASE: 09/19/2001

CIA-RDP86-00513R001963810003-0

ZANKE, Kh.

ZANKI, Kh.

Geographical science in the German Democratic Republic. Izv. AN
(WIRA 11:1)

SSSR. Ser. geog. no.6:134-144 N-D *57.
(Germany, Mast-Geography—Study and teaching)

"APPROVED FOR RELEASE: 09/19/2001


CIA-RDP86-00513R001963810003-0

USSR/Geophysics - Erosion Nov/Dec 52

"Erosional Forms of Relief Which are Due to Seasonal Water Flow, and Their Principles of Forest Improvement," G. V. Zanin, Inst of Geog, Acad Sci USSR

"Iz Ak Nauk SSSR, Ser Geograf" No 6, pp 10-23

Discusses fixed erosional forms and forms of recent washouts. Suggests afforestation and simple engineering techniques of construction to decrease flow to prevent erosion.



BRITSINA, M.P.; GERASINOV, I.P.; EHIVAGO, A.V.; ZANIN, G.V.; FEDOROVICH, B.A.

IUrii Sergeevich Kashin; obituary. Izv.AH SSSR Ser.geog. no.6:92-93 N-D '53, (MLRA 6:12)

(Kashin, Iurii Sergeevich, 1921-1953)


Dissertation: "Primitive and Present-Day Erosion Forms of Relief of the Oksko-Donskoye Flain and Its Interrelation." Cand Geog Sci, Inst of Geography, Acad Sci USJR, 21 May 54. Vechernyaya Moskow, Noscow, 12 May 54.

SO: SUM 284, 26 Nov 1954.

ZANIN, G.V.; ALKESANDROVA, V.D.; KRAVTSOVA, V.I.; SHAVRYGIN, P.I.

Division into natural regions of the new reclaimed farm lands in the Altai Territory. Izv.AN SSSR. Ser.geog. no.2:69-72 Mr-Ap '55.

(Altai Territory--Physical geography) (MLRA 8:6)




	Recent ravine erosion in the Altai plains and its contrl.	Isv.
	AN SSSR. Ser.geog. no.6:43-49 N-D '62. (1	(IRA 15:12)
	1. Institut geografii AN SSSR. (Altai Territory—Erosion)	
,		
•		

GAL'TSOV, A.P.; GERASIMOV, I.P.; ZANIN, G.V.; SOBOLEV, L.N.

Scheme of the general program for station field research on the biogeophysics of natural landforms. Izv. AN SSSR. Ser. geog. no.5:95-99 S-0 '61. (MIRA 14:9)

1. Institut geografii AN SSSR. (Physical geography--Research)



ZANIH, G.V.

Origin of some barrier lakes and continental deltas of mountain rivers in the Polar Urals. Izv. AN SSSR. Ser. geog. no.6:66-68 N-D '60.

(MIRA 13:10)

1. Institut geografii AN SSSR. (Ural Hountains--Iakes)

(Ural Mountains-Doltas)

3(5)

SOV/10-59-4-11/29

AUTHOR:

Zanin, G.V.

TITLE:

Nivosolifluction and Suffosion Landforms in the

Altay Lowlands

PERIODICAL:

Izvestiya Akademii nauk SSSR, Seriya geografiches-

kaya, 1959, Nr 4, pp 91 - 96 (USSR)

ABSTRACT:

The article deals with the phenomena of snow-caused soil creep and soil sagging due to underground washout as encountered in the Pavlovskiy and Shelabolakhin-skiy rayony (Pavlovsk and Shelabolakhia Rayons) of the Ob'plateau, Altayskiy Kray, in spring 1955. They appear on the ravine slopes exposed to the north as wide, karren-like niches (Figures 1 to 6) and on the flat country as soil depressions (Figures 7 and 8). These phenomena are due to the peculiarities of the Altay loess-like loam formations and their thickness (15-80 m), which originated in the Quaternary period. As snow in this area tends to melt away rather late (in

Card 1/2

SOV/10-59-4-11/29

Nivosolifluction and Suffosion Landforms in the Altay Lowlands

1955, it melted as late as 15-20 May), the slopes of the ravines are subject to landslides and the flat country to sags, the latter in the shape of caves, sink holes, and underground channels up to 1.5 to 2 m in diameter. There are 5 diagrams, 1 set of diagrams, and 2 photographs.

ASSOCIATION: Institut geografii AN SSSR (Institute of Geography

AS USSR)

Card 2/2

15-57-5-5942D

Translation from: Referativnyy zhurnal, Geologiya, 1957, Nr 5,

p 32 (USSR)

AUTHOR:

Zanin. G. V.

TITLE:

Ancient and Contemporary Erosional Relief Forms on the Oka-Don Plain and Their Interrelationships (Drevniye i sovremennyye erozionnyye formy rel'yefa Oksko-Donskoy ravniny i ikh vzaimootnosheniya)

ABSTRACT:

Bibliographic entry on the author's dissertation for the degree of Candidate of Geographical Sciences,

Moscow. 1954.

ASSOCIATION:

Moscow, 1954.

Card 1/1

ZANIN, M.I.

AUTHORS:

Golub, B. I., and Zanin, M. I.

TITLE:

Automatic Switch on Machines for Tests for Fatigue under Torsion Avtomaticheskiy vyklyuchatel k mashinam dlya ispytaniya na

ustalost' pri kruchenii)

PERIODICAL:

Zavodskaya Laboratoriya, 1957, Vol. 23, No. 1, pp. 104-105 (U.S.S.R.)


ABSTRACT:


The authors find that in the designing of a cutout switch for machines, testing for fatigue under torsion is made difficult by the fact that there is practically no displacement either of the part tested or some part of the machine. They have developed a cutout switch for the machine with a torsion dynamometer. Contact is effected between a plunger and mercury under given conditions of vibration, causing a current to operate the switch. The details of the mechanism are explained with a drawing of the mercury circuit-closing device and the lagout of the switch circuit. There


are no references cited.


ASSOCIATION:

Card 1/2










IMSHENETSKIY, A.A., akademik; YEFIMOCHKINA, Ye.F.; NIKITIN, L.Yo.; ZANIN, V.A.

Bactorial decomposition of cholesterol in the human blood serum.

Dokl. AN SSSR 161 no.3:701-703 Mr '65.

(MIRA 18:4)

1. Institut mikrobiologii AN SSSR.



ZANIN, Vadim Ivanovich; ISAYEV, Ye.N., kand. ekon. nauk, otv. red.;

SNITSARENKO, A.A., red.; YELISTRATOVA, Ye.M., tekhn. red.

[Working time and labor productivity] Rabochee vremia i

proizvoditel'nost' trude. Novosibirsk, Izd-vo Sibirskogo

otd-nia AN SSSR, 1963. 114 p. (MIRA 16:10)


(Labor productivity) (Time study)


ZANIN, V.I.

Utilization and Planning of Work Time

The following dissertations were defended in the Joint Scientific Council on the Economic Sciences and the Humanities, Candidate of Economic Sciences.

Vestnik Akad Nauk, No. 4, 1963 pp. 119-145





BERLIN, I.A.; ZANINA, A.A.; YECOROVA, A.Yu.

Some characteristics of the diurnal variation of the air temperature and relative humidity on the territory of the U.S.S.R. Trudy GGO no. 112:176-186 *63. (MIRA 17:5)

之前和10年二

AUTHOR: Zanina, A.A.

Characterization of Temperature Anomalies Under Conditions

36-65-8/10

of the Mountainous Relief and Coastal Plains of

Scandinavia (O kharakteristikakh temperaturnykh anomaliy

v usloviyakh gornogo rel'yefa i poberezh'ya)

FERIODICAL: Trudy Glavnoy geofizicheskoy observatorii, 1956, Nr 65(127).

pp. 83-92 (USSR)

ABSTRACT: This is an extensive study of the spatial and temporal

distribution of temperature anomalies in the complex physico-geographical conditions of the Scandinavian peninsula, where the influence of subjacent surfaces is particularly strong and where the transition from mine to continental conditions occurs very quickly.

There are 6 figures and 3 references, all USSR.

AVAILABLE: Library of Congress

Card 1/1

TITLE:

ZANINA, Anastaciya Andreyevna; IEBEDEV, A.N., kand. geogr. nauk, red.; VAYTSARI, A.I., red.

[Climate of the Scandinavian poninsula] Klimat Skandinavskogo poluostrova. Leningrad, Gidrometecizdat, 1964. 51 p.

(MIRA 17:7)

3(7)

PHASE I BOOK EXPLOITATION

SOV/1819

Zanina, Anastasiya Andreyevna

- Dal'nevostochnyye rayony, Kamchatka i Sakhalin (Far East Regions: Kamchatka and Sakhalin) Leningrad, Gidrometeor. izd-vo, 1958. 166 p. (Series: Klimat SSSR, vyp. 6) Errata slip inserted 1,200 copies printed.
- Sponsoring Agencies: USSR. Glavnoye upravleniye gidrometeorologicheskoy sluzhby, and Glavnaya geofizicheskaya observatoriyz. im. A.I. Voyeykova.
- Resp. Ed.: T.V. Pokrovskaya; Ed: L.P. Zhdanova; Tech. Ed.: O.G. Vladimirov.
- PURPOSE: This book is intended for climatologists, agrometeorologists, and geographers, as well as for vuz students.
- COVERAGE: This book describes the characteristics of the basic climate-forming factors (the peculiarities of the radiation budget, the circulation processes, the effect of relief and Card 1/6

Far East Regions: Kamchatka and Sakhalin

SOV/1819

sea). It presents a brief outline of seasonal climates, and a description of the individual climatic factors (thermal and wind conditions, humidity rate) in the Far East. The book is the 6th volume of a series entitled "Klimat SSSR". The series treats the following regions: 1. European Territory, 2. Caucasus, 3. Central Asia, 4. Western Siberia, 5. Eastern Siberia, 6. Far East Regions: Kamchatka and Sakhalin. There are 46 references of which 44 are Soviet and 2 English.

TABLE OF CONTENTS:

Preface

3

SECTION I. THE FORMATION OF CLIMATE

Ch. 1. The Radiation Factors of Climate

7

Sunshine (7). Total solar radiation (12). The absorbed radiation (15). The effective radiation (18). The radiation balance (19).

Card 2/6

Far Eas	t Regions: Kamchatka and Sakhalin	sov/1819
Ch. 2.	The Circulation Factors of Climate	22
	General characteristics of circulation processes (22). Special Circulation Features According to Seasons. Winter Circulation (2 Summer Circulation (30). Circulation During Transitional Seasons (34).	24).
Ch. 3.	The Importance of the Subjacent Surface The effect of relief (36). The Effect of Bo Seas and Inland Waters (39).	36 ordering
	SECTION II. GENERAL CHARACTERISTICS CLIMATE	S OF
Ch. 4.	A Brief General Outline Winter (42). Spring (44). Summer (45). Auto	41 umn (46).
Ch. 5.	Thermal Conditions Winter (49). Spring (56). Summer (63). Auto	47 umn (69)
Card 3/		

Far East l	Regions: Kamchatka and Sakhalin SOV/18	19
	Wind Conditions (Local Winds (79)	73
Ch. 7.	Humidity Conditions The Moisture of Air (81). Cloudiness (86). Precipitation (88) Evaporation and Runoff (103). Snow Cover (106)	. 80
ch. 8.	Atmospheric Phenomena Fogs (111) Snowstorms (117). Thunderstorms (118). Glaze and Sleet (119).	111
SEC	TION III. THE CLIMATIC FEATURES ACCORPING TO REGIO	NS
	Chukutsko-Anadyrskiy Rayon Winter (123). Spring (125). Summer (126). Autumn (128).	123
Ch. 10.		129
Card 4/6		


Control to the first for the Single	به المناصلية حداثية الأفيار بمورودة في	A SALID - Clare control Salid Special Asia Asia Asia Special Control C	
	Far East	Regions: Kamchatka and Sakhalin	sov/1819
	Ch. 11.	Lower (Eastern) Priamur'e (Amur Region) Winter (133). Spring (135). Summer (135). Autumn (136)	132
	Ch. 12.	Central (Western) Priamur'e Winter 138). Spring (139). Summer (139). Autumn (140)	137
	ch. 13.	Primorskiy Kray Winter (142). Spring (142). Summer (143). Autumn (144)	140
	Ch. 14.	Kamchatka and Komandroskiye Islands Kamchatka. Winter (145). Summer (145). Kom dorskiye Island. Winter (148). Summer (149). Spring (149). Autumn (149).	144 nan~
	Card 5/6		
EAST OF BRIDE STATE	Property of the second of the		


Far East Regions: Kamchatka and Sakhalin	SOV /1010
Ch. 15. Sakhalin and Kuril Talanda	SOV/1819 149
Sakhalin. Winter (151). Summer (152). Spring Autumn(153). Kudril Islands. Winter (154). Spring (154). Summer (154). Autumn (154). Literature	(193)
Appendix	155
AVAILABLE: Library of Congress	157
Card 6/6	
MM/ad 6-15-59	
	9.3

ZANINA, Anastasiya Andreyevna; POKROVSKAYA, T.V., otv.red.; ZHDANOVA, L.P., red.; VLADIMIROV, O.G., tekhn.red.

[Regions of the Far East, Kamchatka, and Sakhalin] Del'nevostochnye raiony, Kamchatka i Sakhalin, Leningrad, Gidrometeor, 12d-vo, 1958, 166 p. (Klimat SSSR, no.6) (MIRA 12:2)

(Soviet Far East-Climate)





S/076/61/035/001/016/022 B004/B060

AUTHORS:

Marshakov, I. K. and Zanina, A. N.

TITLE:

Mechanism of the corrosive destruction of iron along the

water line

PERIODICAL:

Zhurnal fizicheskoy khimii, v. 35, no. 1, 1961, 206-211

TEXT: The authors were concerned with the problem of the intensive corrosion of low-alloy steels along the water line, i.e., along the line separating the corroding medium from the atmosphere. According to I. L. Rozenfel'd and K. A. Zhigalova (Ref. 1) the process has a different course depending on whether the electrolyte surface remains immobile, or whether its level fluctuates. The corrosion of Armco iron was examined in various media with the surface at rest. The formation of differential aeration couples was observed. Fig. 1 shows the element "metal in water line - metal dipped in electrolyte". The following results were obtained: An intensive corrosion appeared along the water line in acid media and in neutral solutions containing inhibitors such as bichromates, nitrates, or phosphates. The iron did not undergo any intensive corrosion along the

Card 1/3

av pasaceral


88712

Mechanism of the corrosive destruction ...

\$/076/61/035/001/016/022 B004/B060

water line in neutral chlorides and sulfates. An intensive local destruction may take place, however, in media with a low electrical conductivity. Due to the difference in access of oxygen to the iron of the water line and iron dipped into the electrolyte, differential aeration couples are formed, the anode being provided by the iron dipped into the electrolyte. In media with a low electrical conductivity (tap water) the currents of these elements concentrate and give rise to intensified corrosion somewhat below the water line. The intensive etching of iron along the water line in acid media is not, as hitherto assumed, caused by a stronger precipitation of the corrosion products at the water - air interface, but by the action of corrosion macrocells, whose anode is the Fe in the water line. The cause of the formation of such cells is the rapid increase of the pH of the electrolyte which forms the meniscus. In neutral electrolytes containing inhibitors, the corrosion of Fe is similar to that in narrow slits and crevices. Due to an impeded access of the inhibitor to the electrolyte forming the meniscus there arise active passive cells, which give rise to the intensive corrosion. There are 4 figures, 1 table, and 9 references: 6 Soviet-bloc and 2 non-Soviet-bloc.

Card 2/3



MARSHAKOV, I.K.; ZANINA, A.N.

Mechanism of the waterline corrosion of iron. Zhur. fiz. khim. 35 no.1:206-211 Ja '61. (MIRA 14:2)

1. Voronezhskiy gosudarstvennyy universitet. (Iron—Corresion)


ZANINA, A.S.: LIPOVICH, V.G.


KOTLYAREVSKIY, I.L.; ZANINA, A.S.: LIPOVICH, V.G.

Aromatization of divinylacetylene. Izv.vost.fil.AM SSSR no.4/5:90-99
(EIRA 10:9)

157.

1. Vostochno-Sibirskiy filial Akademii nauk SSSR.
(Acetylene) (Aromatic compounds)







AUTHORS:

Kotlyarevskiy, I.L. and Zanina, A.S.

sov/80-59-1-35/44

TITLE:

Synthesis of \mathcal{B} -Methyl Naphthalene (Sintez \mathcal{B} -metilnaftaline) Sixth Communication (Soobshcheniye VI)

PERIODICAL:

Zhurnal prikladnoy khimii, 1959, Nr 1, pp 207-210 (USSR)

ABSTRACT:

in the previous papers of this series (this is the 6th one from the series of unsaturated hydrocarbons studies), the authors showed that the divinylacetylene and its alkyl derivatives can be completed into aromatic hydrocarbons under the effect of certain catalyzers, such as aluminum oxide, chrome oxide, etc. This reaction can be used for the synthesis of aromatic hydrocarbons with a prescribed structure. The authors carried out the aromatization of isopropenylcyclohexenylacetylene which resulted in obtaining \$\beta\$-methyl naphthalene. When the 2-methyl-4-(cyclohexene-1-yl)-butene is used in the process of aromatization the yield and individuality of the substance are increased. There are 2 tables and 4 Soviet references.

SUBMITTED:

March 2, 1957

APPROVED FOR RELEASE: 09/19/2001 CIA-RDP86-00513R001963810003-0"

Card 1/1

507/153-2-4-26/32 Kotlyarevskiy, I. L., Fisher, L. B., Zanina, A. S., Terpugova, 5(1,3) AUTHORS: M. P., Volkov, A. N., Shvartsberg, M. S. Synthesis of Several Monomers on Alumochromium Catalysts TITLE: PERIODICAL: Izvestiya vysshikh uchebnykh zavedeniy. Khimiya i khimicheskaya tekhnologiya, 1959, Vol 2, Nr 4, pp 608 - 613 (USSR) A report on this paper was given at the All-Union Conference on "Ways of Synthesis of Initial Products for the Production ABSTRACT: of High Polymers" which took place in Yaroslavl' from September 29 to October 2, 1958. The results of the catalytic synthesis of 2,3-dimethyl-butadiene-1,3 as well as of monomers of the type of p-xylene from acetylene derivatives are given. The substance mentioned at first can be used in the production of special rubber types (Ref 1). It could not be obtained by the production methods so far used. The diagram (see Diagram) being worked at by the authors consists of two stages. The first one (Ref 2) yielded not more than 15% of the end product. In spite of numerous patents (Ref 3), a thorough description of reaction conditions is still missing. Therefore, the authors determined the optimum conditions of isobutane alkylation with ethylene Card 1/4

Synthesis of Several Monomers on Alumochronium Catalysts SOV/153-2-4-26/32

in the presence of aluminum chloride. Under these conditions (48 - 510, 7 - 9 atm, 1.5 kg isobutane, 145 g ethylene, 40 g C2H5C1, 5 g AlC13, 2 hours) the yield of 2,3-dimethyl-butane rises to 47%. The reaction is very sensitive to temperature (only 1/3 of the alkylate yield at 350). The catalyst can be used 5 to 6 times without reducing the quantity of alkylate or of 2,3-dimethyl-butane. Ethylene has to be added during the whole process: its partial pressure must not exceed 0.5 - 0.7 atm, or otherwise the 2,3-dimethyl-butane content in the alkylate decreases rapidly. The addition of 1-3% CoH501 accelerates the process. Isotutane alkylation with ethylene at a high temperature proceeds at a pressure of 100 - 200 atm according to a radical mechanism, and is accelerated by radical donors. It was carried out by the authors in the presence of CoHcCl (for the first time) in a special, continuously working plant. The alkylate yield (computed for ethylene) reached 170-180% under

first time) in a special, continuously working plant. The alkylate yield (computed for ethylene) reached 170-180% under optimum conditions (450°, 200 atm, reaction time 25 minutes, weight ratio isobutane: ethylene = 10:1, initiator quantity 2.5%). 2,2-Dimethyl-butane (32-35% of the alkylate) was the

Card 2/4